

LED strips

DESCRIPTION

Constant voltage LED strip 230Vdc, 50m roll
Ideal for different environments, indirect, accent, decorative lighting
Lighting of aluminium mouldings and profiles



SUMMARY TABLE

Reference	Power (W/m)	Flow (lm/m)	Color T° (K)
BX3-220-60-50M-CW	10 W	1630	6000
BX3-220-60-50M-W	10 W	1630	4000
BX3-220-60-50M-WW	10 W	1579	3000
BX3-220-60-50-RGB	10 W	-----	RGB

CHARACTERISTICS


Voltage	230V
Power	10 W/m
Total power	500 W / 10W RGB
Protection index	IP 65
Wide strip	8 mm
Roll meters	50m / 1m RGB
EPREL Classification	G
CCT	6000/4000/3000K
At-risk group	GR0
CRI	>80
Luminous efficacy	Up to 160 lm/W

CHARACTERISTICS

Isolation	0.5 Kv
Opening Angle	120°
Type of Led	SMD 5050
Shelf life	40000h
Regulation	Yeah
Tc	75°C
Operating Temperature	-10°C to 25°C
Degrees of opening	120°

DIMENSIONS

Ref.	Long (m)	Broad (mm)	High (mm)	Weig ht (Kg)
COB-320	50	12mm	-----	1.5



PHOTOMETRY

