

LED strips

DESCRIPTION

Constant voltage LED strip 230Vdc, 5m roll
Ideal for different environments, indirect, accent, decorative lighting
Lighting of aluminium mouldings and profiles



SUMMARY TABLE

Reference	Power (W/m)	Flow (lm/m)	Color T° (K)
BX3-R5031072W2-CW	14.4 W	1375	6000
BX3-R5031072W2-W	14.4 W	1375	4000
BX3-R5031072W2-WW	14.4 W	1296	3000

CHARACTERISTICS


Voltage	24V
Power	14.4 W/m
Total power	72 W
Protection index	IP 20
Wide strip	13 mm
Roll meters	100 m
EPREL Classification	G
CCT	6000/4000/3000K
At-risk group	GR0
CRI	>80
Luminous efficacy	Up to 95.4 lm/W

CHARACTERISTICS

Isolation	0.5 Kv
Opening Angle	120°
Type of Led	SMD 5050
Shelf life	40000h
Regulation	Yeah
Tc	75°C
Operating Temperature	-10°C to 25°C
Degrees of opening	120°

DIMENSIONS

Ref.	Long (m)	Broad (mm)	High (mm)	Weight (Kg)
220352860	5	10mm	-----	0.9



PHOTOMETRY

