

HIGH BAY LED bell

IP65

IK
08



DESCRIPTION

Luminaire for high heights, with high efficiency
Made of high quality aluminum, with different beam openings
For better light distribution.

SUMMARY TABLE



Reference	Power (W)	Max. luminaire flux (lm)		Installation height (m.)
		4000 K	6000 K	
BX3-HB-100WK-xx	100 W	10000	10000	5-6
BX3-HB-150WK-xx	150 W	15000	15000	6-7
BX3-HB-200WK-xx	200 W	20000	20000	8-9

CHARACTERISTICS

Material	Aluminum casting
Diffuser	Polycarbonate
Finish	Black
Protection index	IP 65
Impact protection	IK 08
Voltage	220-240 V
Frequency	50/60 Hz
Power factor	>0.95
Insulation class	Class I
CCT	6000K / 4000 K
CRI	>80
Luminous efficacy	Up to 100 lm/W
Shelf life	L70B10 50,000h
Regulation	No
Facility	Suspended
Driver	Internal
Operating Temperature	-10°C to 25°C
Degrees of opening	120°

DIMENSIONS

Power (W)	Diameter (mm)	High (mm)	Weight (Kg)
100	300	160	1.4
150	350	160	2.0
200	400	194	2.6



PHOTOMETRY

