

HIGH BAY LED bell

IP65

IK
08

DESCRIPTION

Luminaire for high heights, with high efficiency
Made of high quality aluminum, with different beam openings
For better light distribution.



SUMMARY TABLE



Reference	Power (W)	Max. luminaire flux (lm)		Installation height (m.)
		4000 K	6000 K	
BX3-HVB100W-N2-xx	100 W	11000	11000	5-6
BX3-HVB150W-N2-xx	150 W	16500	16500	6-7
BX3-HVB200W-N2-xx	200 W	22000	22000	8-9

CHARACTERISTICS

Material	Aluminum casting
Diffuser	Polycarbonate
Finish	Black
Protection index	IP 65
Impact protection	IK 08
Voltage	220-240 V
Frequency	50/60 Hz
Power factor	>0.95
Insulation class	Class I
CCT	6000K / 4000 K
CRI	>70
Luminous efficacy	Up to 110 lm/W
Shelf life	L70B10 50,000h
Regulation	No
Facility	Suspended
Driver	Internal
Operating Temperature	-10°C to 25°C
Opening angle	120°

DIMENSIONS

Power (W)	Diameter (mm)	High (mm)	Weight (Kg)
100	244	43	2
150	286	43	3
200	325	43	4



PHOTOMETRY

