

HIGH BAY ADJUSTABLE LED bell

IP65

IK
08



DESCRIPTION

Luminaire for high heights, with high efficiency
Made of high quality aluminum, with different beam openings
For better light distribution.

SUMMARY TABLE



Reference	Power (W)	Max. luminaire flux (lm)		Installation height (m.)
		4000 K	6000 K	
BX3-HVB100WP3-xx	100 W	17000	17000	5-6
BX3-HVB150WP3-xx	150 W	25500	25500	6-7
BX3-HVB200WP3-xx	200 W	34000	34000	8-9

CHARACTERISTICS

Material	Aluminum casting
Diffuser	Polycarbonate
Finish	Black
Protection index	IP 65
Impact protection	IK 08
Voltage	220-240 V
Frequency	50/60 Hz
Power factor	>0.95
Insulation class	Class I
CCT	6000K / 4000 K
CRI	>80
Luminous efficacy	Up to 170 lm/W
Shelf life	L70B10 70,000h
Regulation	0-10V
Facility	Suspended
Driver	Internal
Operating Temperature	-10°C to 25°C
Degrees of opening	120°

DIMENSIONS

Power (W)	Diameter (mm)	High (mm)	Weight (Kg)
100	295	115	2.9
150	400	115	3.9
200	550	115	4.9



PHOTOMETRY

