

## LED downlight

### DESCRIPTION

Downlight, surface mounted, round, with a degree 120° opening for better uniformity.  
Made of aluminum and opal diffuser



### SUMMARY TABLE



| Reference         | Power (W) | Max. luminaire flux (lm) | CCT color temperature (K) |
|-------------------|-----------|--------------------------|---------------------------|
| BX3-MZMD01-12W-CW | 12 W      | 930                      | 6000                      |
| BX3-MZMD01-12W-W  | 12 W      | 930                      | 4000                      |
| BX3-MZMD01-12W-WW | 12 W      | 874                      | 3000                      |

### CHARACTERISTICS

|                       |                 |
|-----------------------|-----------------|
| Material              | Aluminum        |
| Diffuser              | Opal            |
| Finish                | White           |
| Protection index      | IP20            |
| Retinal risk          | GR0             |
| Voltage               | 220-240 V       |
| Frequency             | 50/60 Hz        |
| Power factor          | >0.95           |
| Insulation class      | Class II        |
| CCT                   | 6000/ 4000/3000 |
| CRI                   | >80             |
| Luminous efficacy     | Up to 66 lm/W   |
| Shelf life            | L70B50 40,000h  |
| Regulation            | No              |
| Driver                | Abroad          |
| Facility              | Surface         |
| Operating Temperature | -10°C to 25°C   |
| Degrees of opening    | 120°            |

### DIMENSIONS

| Power (W) | Diameter (mm) | Diameter of fence (mm) | High (mm) | Weight (Kg) |
|-----------|---------------|------------------------|-----------|-------------|
| 12 W      | 170           | 21                     | 37        | 0.29        |



### PHOTOMETRY

