

SUPERSLIM LED panel

DESCRIPTION

LED panel, with high efficiency,
Lowest luminaire on the market
Made of aluminum and opal diffuser



SUMMARY TABLE

Reference	Power (W)	Max. luminaire flux (lm)	CCT color temperature (K)
BX3-PANMB59559536W-CW	36 W	3623	6000
BX3-PANMB59559536W-W	36 W	3623	4000
BX3-PANMB59559536W-WW	36 W	3495	3000
BX3-PAN120060072W-CW	72 W	7900	6000
BX3-PAN120060072W-W	72 W	7900	4000
BX3-PAN120060072W-WW	72 W	7790	3000

CHARACTERISTICS

Material	Aluminum
Diffuser	Opal
Finish	White
Protection index	IP 40
Retinal risk	GR0
Voltage	220-240 V
Frequency	50/60 Hz
Power factor	>0.95
Insulation class	Class II
CCT	6000K / 4000K
CRI	>80
Luminous efficacy	Up to 100 lm/W
Shelf life	L70B50 50,000h
Regulation	No
Driver	External
Facility	Suspended/Recessed
Operating Temperature	-10°C to 25°C
Degrees of opening	120°

DIMENSIONS

Power (W)	Long (mm)	Broad (mm)	High (mm)	Weight (Kg)
36	600	600	12	2.4
72	1200	600	12	4.9



PHOTOMETRY

